

FLOODLINE Stainless Steel Point Sensor



The Floodline Point Sensor is a compact sensor for vertical or horizontal mounting. Water touching its stainless steel probes activates the alarm. Used with the stainless steel Floodline Guard Plate to give heavy duty physical protection and assist fixing and adjustment.

The Point Sensor is used where Detection Cable could be damaged or where some damp, minor wetting or spillage is expected or of little concern.

The sensor can be connected in any number and/or combination with other Floodline sensors.

Applications:

- Plant rooms
- Solid floor area
- Basement/tunnels

Detection:

- Activates when any conductive liquid makes contact across the probes.
- Multiple re-use.
- Instant return to use after water is cleared up.

Construction:

- High density plastic body, stainless steel/nickel plated brass probes.
- Heavy duty, stainless steel Guard Plate.
- Encapsulation option for immersion proofing.

Dimensions:

- Sensor: H71mm x W44mm x D25mm.
- Guard Plate: H110mm x W105mm x D30mm.

Fixing:

- Base of wall or apparatus.
- Floor - free standing or fixed.
- Tank/Sump etc. – requires immersion proofing.
- Two versions available – vertical or horizontal orientation.

System:

- Connected in any number and/or combination with other Floodline sensors.



FLD Point Sensor Metal Guard 15.03.2022 Rev.0